



GRASS CROSS SPACERS

Cross spacers for laying setts for a stable area with integrated eco greenery spacer.

Certified to DIN EN ISO 9001:2008

Application: For laying setts on courtyards, pathways and garage drives.

Dimensions: Grass cross spacer
(width × height × total length in mm)
30 × 55 × 70 mm (prod. no. 4022514**175117**)

T-shape grass spacer
30 × 55 × 70 mm (prod. no. 4022514**175223**)

Can be used for laying setts with grass, silica sand or fine stone chipping joints (chippings not bigger than 4 mm) in a customary crushed stone bed in stack bond or running bond pattern.

NOTE:

When being used on courtyards and garage drives subsequently to be driven on by cars, the grass cross spacers must additionally be stabilised using water-permeable single grain mortar (e.g. from Schomburg, PCI Pavifix or other suppliers).

NOTE:

After the setts are laid, the area should be compacted before the joints are filled in, as otherwise the cross spacers will get pushed back up and become visible.

Material: Polypropylene (PP), recycled, reprocessed and environmentally compatible

Technical data: Polypropylene (PP), recycled, reprocessed and environmentally compatible
Gross density: 0.895 - 0.92 g/cm³
Resistant to deformation from -10 to +110°C
Minimal water absorption
Flammability classification as per UL 94 = HB (equivalent to B2)



Methods of use 08/2015 Our verbal and written recommendations in respect of technical application that we provide based on our experience to assist the purchaser/user are in line with current theoretical and practical knowledge. Neither they nor any external calculations are binding or create any legal contractual relationship or any additional obligations arising from the purchase contract. They do not absolve purchasers/users from the need to check for themselves that our products are suitable for their intended purpose.